




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>A61B 5/00</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 95/21565</b> <b>(43) International Publication Date:</b> 17 August 1995 (17.08.95)
<b>(21) International Application Number:</b> PCT/US95/01804 <b>(22) International Filing Date:</b> 14 February 1995 (14.02.95) <b>(30) Priority Data:</b> 08/195,654 15 February 1994 (15.02.94) US <b>(71) Applicant:</b> FUTREX, INC. [US/US]; Suite 620, 6 Montgomery Village Avenue, Gaithersburg, MD 20879 (US). <b>(72) Inventors:</b> ROSENTHAL, Robert, D.; 9805 Hallowell Place, Gaithersburg, MD 20879 (US). YABE, Ryoichi; 2-11-5-509, Takasago, Katsushika-ku, Tokyo 125 (JP). <b>(74) Agents:</b> NEWLAND, Bart, G. et al.; Rothwell, Figg, Ernst & Kurz, 555 Thirteenth Street, N.W., Suite 701 East, Washington, DC 20005 (US).		<b>(81) Designated States:</b> AU, CA, JP, MX, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

**(54) Title:** APPARATUS FOR PREVENTING FINGER MOTION DURING OPTICAL MEASUREMENTS**(57) Abstract**

A method and apparatus for preventing undesirable index finger rotational motion within a non-invasive quantitative blood analyte measurement instrument (10) includes placing at least the middle finger or the thumb into proper alignment with the index finger when inserted in the instrument (10) to prevent the index finger from rotating with respect to the instrument's optical axis. The natural pincer-type relationship of the thumb and index finger is used to align the index finger in the optical axis by the positioning of the thumb and the positioning of the middle finger is used to hinder the rotation of the finger towards the thumb away from the optical axis. Conductive material is provided in grooves formed on the instrument housing to dissipate EMI energy from the test subject.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

## APPARATUS FOR PREVENTING FINGER MOTION DURING OPTICAL MEASUREMENTS

BACKGROUND OF THE INVENTIONCross-Reference to Related Applications

5           This application is a continuation-in-part of co-  
pending application Serial No. 08/103,758, filed August  
10, 1993, which is a continuation-in-part of Serial No.  
07/813,739, filed December 30, 1991 and now U.S. Patent  
5,237,178, which is a continuation-in-part of Serial  
10 No. 07/565,302, filed August 10, 1990, now U.S. Patent  
5,077,476, which is a continuation-in-part of  
application Serial No. 07/544,580, filed June 27, 1990,  
now U.S. Patent No. 5,086,229.

Field of the Invention

15           This invention relates to instruments for the non-  
invasive quantitative measurement of constituents in  
blood, such as blood glucose levels. Specifically,  
this invention relates to an improved analysis  
instrument which achieves improved accuracy in  
20 measurement by ensuring that the position of the  
subject's finger in the instrument remains constant  
each time the finger is inserted into the instrument.

Description of the Background Art

25           Information concerning the chemical composition of  
blood is widely used to assess the health  
characteristics of both people and animals. For  
example, analysis of the glucose content of blood  
provides an indication of the current status of

metabolism. Blood analysis, by the detection of above or below normal levels of various substances, also provides a direct indication of the presence of certain types of diseases and dysfunctions.

5       A current type of blood glucose analytical instrumentation is available for the specific purpose of determining blood glucose levels in people with diabetes. This technology uses a small blood sample from a finger poke which is placed on a chemically  
10       treated carrier and is inserted into a portable battery operated instrument. The instrument analyzes the blood sample and provides a blood glucose level reading in a short period of time.

      A different class of blood glucose analytical  
15       instruments is the near-infrared quantitative analysis instrument which noninvasively measures blood glucose, such as the type described in U.S. Patent No. 5,077,476, incorporated by reference herein. The noninvasive blood glucose measurement instrument  
20       analyzes near-infrared energy following interactance with venous or arterial blood, or transmission through a blood-containing body part. The instrument measures a change in light absorption that occurs, in part, due to the glucose content of the blood stream.

25       Non-invasive measurement instruments of this type have broad applications for the diabetic community. For example, people with diabetes have wide changes in their blood glucose content during the day which often require multiple measurements per day for good disease  
30       control. The ability to make these near-infrared blood glucose level measurements noninvasively means that more measurements will likely be made per day than would be made using the more painful blood drawing approach.

An example of a non-invasive measurement instrument is disclosed in U.S.P. 5,086,229, also incorporated by reference herein, wherein an individual user places the most distal portion of his or her finger within a "jaws" type arrangement. Near-infrared energy within the spectrum of interest is then impinged upon the surface of the finger and a detector is placed axially with the near-infrared beam on the opposite side of the finger to receive any near-infrared energy emerging therefrom. A microprocessor receives the amplified signal from the detector and calculates the user's blood glucose level. The near-infrared energy is within a bandwidth of 600-1100 nm, and preferably 600-1000 nm.

Data obtained from experimentation has revealed that the accuracy of such non-invasive measurement of a blood analyte such as glucose is dependent upon the repeatability of proper finger positioning within the instrument. In particular, the inserted finger must be consistently aligned with the optical axis of the instrument. The light path of the near-infrared light source should preferably pass through the center of the cuticle to obtain high accuracy measurements. Thus, it is desirable to avoid rotation of the finger once inserted into the instrument.

There is a natural tendency when grasping an object for the index finger and thumb to form a pincer-type relationship in which the index finger is slightly rotated with respect to the other fingers so that the finger pad on the bottom side of the index finger faces the pad on the bottom side of the thumb.

Fig. 1 illustrates a typical near-infrared measurement apparatus 10 for non-invasive optical measurement of blood analytes. The apparatus has an

aperture (not visible) for insertion of the index finger of the hand 20 of a subject into the optical path of the light source between the light source and detector. In this design, the left index finger is  
5 inserted into the aperture of the unit with the thumb on one side of the unit and the other three fingers on the other side of the unit. As such, the index finger tends to rotate upon insertion to form a pincer-type relationship with the thumb. Dependent on the  
10 particular positioning of the thumb and the other three fingers on the unit during any one insertion, the index finger will assume a different rotational placement within the light path of the instrument.

#### SUMMARY OF THE INVENTION

15 The present invention solves the problems associated with index finger rotation in the conventional apparatus to ensure that the index finger always maintains a consistent positional relationship with the light path of the instrument. As a result,  
20 repeatable accuracy of quantitative blood analyte measurements is improved.

In particular, the present invention provides a method of restraining index finger rotational motion in an optical quantitative measurement apparatus,  
25 comprising the step of causing at least one other finger of the subject to be aligned with the index finger after the index finger has been inserted into the aperture of the instrument, whereby the index finger is prevented from rotating within the aperture  
30 to enable the instrument to provide accurate repeatable quantitative measurements.

The present invention further provides an optical quantitative measurement apparatus having an aperture

for insertion of the index finger of a subject, wherein quantitative measurement of blood analytes is performed by irradiating said index finger with radiation in a predetermined bandwidth, comprising a housing and alignment means provided on the housing for aligning at least one other finger of the subject with the index finger after the index finger has been inserted into the aperture, whereby the index finger is prevented from rotating within the aperture to thereby enable the apparatus to provide accurate repeatable quantitative measurements.

#### BRIEF DESCRIPTION OF THE DRAWINGS

These and other advantages of the present invention will become more fully understood from the following detailed description in conjunction with the accompanying drawings, which are provided by way of illustration only and thus are not limitative of the present invention, and wherein:

Fig. 1 is a plan view of a conventional non-invasive instrument for quantitative measurement of blood analytes;

Fig. 2 is a perspective view of one preferred embodiment of the present invention; and

Fig. 3 is a plan view of another preferred embodiment of the present invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Two alternate methods are provided by the present invention for ensuring that the index finger once inserted into the instrument always maintains a constant positional relationship with the light path within the unit. These two methods can be used individually or in combination, and preferably are used

in combination to achieve the highest level of positioning accuracy.

Referring to Fig. 2, a finger shelf 14 is provided on one side of the unit 10 for placement of the middle finger when the index finger is inserted into aperture 12. The shelf 14 is provided on the left side of the unit when the left hand index finger is used to take the measurement (i.e., for right-handed persons), and correspondingly, the shelf 14 can be equivalently located on the right side of units designed for left-handed persons. Placement of the middle finger on the shelf 14 forces the index finger to remain rotationally centered within the light path of the instrument and prevents the index finger from following the tendency to rotate toward the thumb to a pincer-type relationship. The shelf 14 should be located so that the middle finger rests at a height equal to or slightly above the center line of the index finger when inserted into the instrument. In this way, the index finger assumes the same orientation as the middle finger, allowing the center of the cuticle to remain in the light path. Instead of a shelf, a groove may be equivalently provided in the body of the unit for placement of the middle finger.

A second embodiment of the invention is shown in Fig. 3, wherein the thumb is placed on the bottom edge 16 of the unit 10 in vertical alignment with the index finger inserted in the aperture 12 and with the optical axis of the measuring components. This positional relationship between the index finger and thumb utilizes the natural tendency toward the pincer formation to ensure that the index finger is properly aligned with the optical axis. In a preferred



embodiment, a groove can be formed in the bottom edge 16 for guiding the thumb into the proper location.

Preferably, the instrument is designed to have two grooves in the housing: the first being located on the side of the instrument at an elevation at least equal to the insertion aperture for the index finger or slightly higher, to provide a resting location for the middle finger; and the second being groove being located on the bottom edge of the instrument for guiding the thumb under the index finger in the plane of the optical axis of the equipment. In such manner the index finger is repeatably positioned within the instrument at a constant orientation, preventing rotation and ensuring repeatable measurements of high accuracy.

The present invention further provides elimination of electromagnetic interference (EMI) from the measurement process. EMI can be a major problem because the human body acts as an antenna with respect to the absorption of radio and other energy waves throughout the electromagnetic spectrum. These waves interfere with the proper functioning of the detector in the unit because the detector will receive not only the optical energy from the light source but also the transient and unpredictable EMI energy, and therefore can cause significant measurement errors. EMI is eliminated in the present invention by providing a grounding plate 18 made of conductive material within the groove located on the bottom 16 of the unit, or also within the groove on the side of the unit. The conductive material is connected to the grounding of the electronics within the instrument. When the finger or thumb is in contact with the conductive material, EMI energy is dissipated through the grounding plate 18

and does not interfere with the operation of the detector.

5       The invention having been described, it will be apparent to those skilled in the art that the same may varied in many ways without departing from the spirit and scope of the invention. Consequently, any and all such variations are intended to be included within the scope of the following claims.

What is claimed is:

1. In an optical quantitative measurement apparatus having an aperture for insertion of the index finger of a subject, wherein quantitative measurement of blood analytes is performed by irradiating said index finger with radiation in a predetermined bandwidth, a method of restraining index finger rotational motion comprising the step of:

causing at least one other finger of the subject to be aligned with said index finger after said index finger has been inserted into said aperture;

whereby said index finger is prevented from rotating within said aperture to enable said apparatus to provide accurate repeatable quantitative measurements.

2. A method of restraining index finger rotational motion as set forth in claim 1, wherein said causing step comprises the step of providing means for aligning the middle finger of said subject in a horizontal plane at least as high as a horizontal plane of said index finger.

3. A method of restraining index finger rotational motion as set forth in claim 1, wherein said causing step comprises the step of providing means for aligning the thumb of said subject in the same vertical plane as said index finger.

4. A method of restraining index finger rotational motion as set forth in claim 3, wherein said causing step further comprises the step of providing means for aligning the middle finger of said subject in a horizontal plane at least as high as a horizontal plane of said index finger.

5. A method of restraining index finger rotational motion as set forth in claim 3, wherein said means for

aligning the thumb of said subject comprises a groove formed in the bottom surface of said apparatus into which said thumb is placed, further comprising the step of providing conductive material in said groove connected to ground potential, wherein placement of said thumb in said groove causes said subject to be grounded.

6. An optical quantitative measurement apparatus having an aperture for insertion of the index finger of a subject, wherein quantitative measurement of blood analytes is performed by irradiating said index finger with radiation in a predetermined bandwidth, comprising:

a housing; and

alignment means provided on said housing for aligning at least one other finger of the subject with said index finger after said index finger has been inserted into said aperture;

whereby said index finger is prevented from rotating within said aperture to enable said apparatus to provide accurate repeatable quantitative measurements.

7. An optical quantitative measurement apparatus as set forth in claim 6, wherein said alignment means comprises means for aligning the middle finger of said subject in a horizontal plane at least as high as a horizontal plane of said index finger.

8. An optical quantitative measurement apparatus as set forth in claim 6, wherein said alignment means comprises means for aligning the thumb of said subject in the same vertical plane as said index finger.

9. An optical quantitative measurement apparatus as set forth in claim 8, wherein said alignment means further comprises means for aligning the middle finger

of said subject in a horizontal plane at least as high as a horizontal plane of said index finger.

10. An optical quantitative measurement apparatus as set forth in claim 8, wherein said means for aligning the thumb of said subject comprises a groove formed in the bottom surface of said apparatus into which said thumb is placed, a surface of said groove contacting said thumb comprising conductive material connected to ground potential, whereby placement of said thumb in said groove causes said subject to be grounded.

1/3




FIG. 1

SUBSTITUTE SHEET (RULE 26)

2/3




FIG. 2

SUBSTITUTE SHEET (RULE 26)




FIG. 3



Intern: **11 Application No**  
**PCT/US 95/01804**

According to International Patent Classification (IPC) or to both national classification and IPC

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 A61B G07C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

### C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US,A,4 183 360 (CARLSON ET AL.) 15 January 1980 see column 2, line 62 - column 4, line 11 see figures 1,3-5	1,6
A	---	2,4,5,7, 9,10
Y	US,A,5 077 476 (ROSENTHAL) 31 December 1991 cited in the application see column 3, line 36 - column 4, line 35 see column 7, line 32 - line 62 see figures 1,8A,B	1,6
A	---	1,2,4,6, 7,9
	WO,A,89 01674 (SIEMENS AKTIENGESELLSCHAFT) 23 February 1989 see page 5, line 15 - page 8, line 7 see figures	
	---	
	-/--	

**X** Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

- \* **A** document defining the general state of the art which is not considered to be of particular relevance
- \* **E** earlier document but published on or after the international filing date
- \* **L** document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \* **O** document referring to an oral disclosure, use, exhibition or other means
- \* **P** document published prior to the international filing date but later than the priority date claimed

- "T"** later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X"** document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y"** document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "Z"** document member of the same patent family

Date of the actual completion of the international search

**27 June 1995**

Date of mailing of the international search report

- 6. 07. 95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Chen, A

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 95/01804

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US,A,4 407 295 (STEUER ET AL.) 4 October 1983 see column 4, line 58 - column 5, line 52 see figure 4 ---	1,3,6,8
A	EP,A,0 106 756 (COUSTENOBLE ET AL.) 25 April 1984 see column 9, line 18 - column 12, line 28 see figures 5,8,9 -----	5,10

## INTERNATIONAL SEARCH REPORT

Intern al Application No

PCT/US 95/01804

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-4183360	15-01-80	NONE	
US-A-5077476	31-12-91	US-A- 5086229	04-02-92
		AU-A- 8238791	23-01-92
		CA-A- 2086019	28-12-91
		EP-A- 0536304	14-04-93
		JP-T- 5508336	25-11-93
		NZ-A- 238717	26-08-94
		WO-A- 9200513	09-01-92
		US-A- 5362966	08-11-94
		US-A- 5068536	26-11-91
		US-A- 5204532	20-04-93
		US-A- 5237178	17-08-93
		US-A- 5365066	15-11-94
		US-A- 5218207	08-06-93
WO-A-8901674	23-02-89	EP-A, B 0375706	04-07-90
US-A-4407295	04-10-83	NONE	
EP-A-106756	25-04-84	FR-A- 2533816	06-04-84
		FR-A- 2540376	10-08-84
		FR-A- 2551647	15-03-85
		FR-A- 2551648	15-03-85
		JP-A- 60060836	08-04-85
		US-A- 4596256	24-06-86

THIS PAGE BLANK (USPTO)